

KM-F1050 Specifications

BASIC SPECIFICATIONS:

Configuration:	Desktop Fax with 33.6Kbps Modem and 500 Sheet Cassette, plus Standard Copying, Printing and Scanning Functions		
Compatibility:	ITU-T Group 3		
Scanning Resolution:	Standard:	203 dpi x 96 lpi	
	Fine:	203 dpi x 196 lpi	
	Super Fine:	203 dpi x 391 lpi	
		406 dpi x 391 lpi (interpolated)	
Print Resolution	Fax/Copy:	406 dpi x 391 lpi	
	Print:	600 dpi x 600 dpi*	* Requires Min 4MB of opt DRAM
Fax Memory:	Standard 2MB, Upgradeable to 10MB - Flash Memory		
Memory Capacity:	Std 120 pages/Max 760 pages		
Document Memory Backup:	Std Flash Memory		
Coding System:	MH/MR/MMR/JBIG		
Scanning Method:	CCD		
Print Method:	Laser		
Max Print Width:	8.2"		
Electrical Requirements:	93 - 132V, 47 - 63Hz		
Dimensions:	17.3"W x 17.7"D x 12.2"H		
Weight:	35.2 lbs		

SPEEDS:

Modem Speed:	33.6Kbps - 2.4Kbps with Automatic Fallback
Transmission Speed:	3 spp Super G3
Pages Per Minute:	10.2 Letter Copy & Print

PAPER SUPPLY:

Standard Paper Sources:	500 sheet cassette
Drawer Paper Size:	8.5" x 11"/8.5" x 14"
Std/Max Paper Capacity:	Std 500/ Max 1,250 Sheets
Paper Weight:	16-24 lb Bond

DOCUMENT PROCESSOR:

Type:	ADF
Acceptable Originals:	5.8" x 5" - 11" x 78.7",
Capacity:	70 Sheet
Paper Weight:	12 - 24 lb Bond
Effective Scanning Width:	9.9"
Quick Scan:	1.7 spp

FAX FUNCTION:

DIALING CAPABILITIES:

One-Touch Dialing Keys:	32
Program/One-touch Keys:	8
Speed-dialing Codes:	160
Max. Numbers Stored:	200
Redial Attempts/Intervals:	Up to 5/1 to 15 minutes
Group Dialing:	8 Groups/199 numbers
Other Dialing:	Chain Dialing, Directory Search Dialing, Pulse/Tone Dialing
Max. Dialing Digits:	36

ADDITIONAL FEATURES:

Transmission/Reception: Multi Access, Memory Transmission, Quick Memory Transmission, Delayed Transmission (30 timers), ECM, Auto Fax/Tel. Switch, Polling (232 Locations), Memory polling, Continuous Polling, Verification Stamp, Broadcast Transmission (232 locations), Distinctive ring Detection (DRD), Memory Reception, Delayed Polling, Delayed Multi-Station Polling (30 timers/232 locations), Substitute Reception, Auto Reduction

Security Communication/Codes: Confidential Transmission/Reception (10 mailboxes), Password Communication, Access Codes, Subaddressing Transmission, Department codes (24)

Journals and Lists: Transaction Journal, Communication Journal, One Touch List, Abbreviated Number List, Program List

UTILITIES:

Configuration Editor and Phonebook editor

PRINT:

Std/Max Memory	2MB/Upgradeable to 10MB DRAM
Windows™ OS Compatibility:	Windows 98/Me/NT4.x/2000/XP
Connectivity :	Standard Parallel IEEE 1284
Driver:	Windows GDI
Utilities;	Status Monitor

SCAN:

Resolution:	400 x 400 dpi
File Format:	PDF, TIFF, JPEG, Bitmap
Connectivity:	Standard Parallel IEEE 1284
Scanning Type:	PC Scanning
Driver:	TWAIN
Utilities:	Standard Document Management Software

COPY:

Continuous Copy:	Up to 99
Zoom:	70% to 100%

PAPER HANDLING OPTIONS:

PAPER DRAWER: PF-45

Paper Capacity:	250 Sheets
Paper Weight:	16 - 24 lb Bond
Paper Size:	8.5" x 11", 8.5" x 14", A4
Dimensions/Weight:	16.8"W x 16.4"D x 3.6"H/10.4 lbs

PAPER DRAWER: PF-46

Paper Capacity:	500 Sheets
Paper Weight:	16 - 24 lb Bond
Paper Size:	8.5" x 11", 8.5" x 14", A4
Dimensions/Weight:	16.8"W x 16.4"D x 4.7"H/13.2 lbs

ADDITIONAL OPTIONS:

2MB Flash Memory (MM-15-2), 4MB Flash Memory (MM-15-4), 8MB Flash Memory (MM-15-8)
4MB DRAM (MM-10-4), 8MB DRAM (MM-10-8), Telephone Handset (HS-45)

CONSUMABLES

TK-45	All-in-One Cartridge	12,000 pages@3% Coverage*
*based on ITU-T No. 1 chart in standard mode		
Ships with one TK-45 All-in-One Cartridge		



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com.
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2003 Kyocera Mita America, Inc.

Item Code# 87164139



www.kyoceramita.com